



Driginal post set 1820 by Laughlin with witnesses: 24" poplar S 48 W 13 links, 12" sugar S 61 E 43 links per Marion County Atlas pg. 8. Hosbrook 8-18-1853 called no stone; but witnesses: 18" sugar N 52 E 59 linsk and 14" hickory S 34 E 63 links per Pike Township Legal Survey Book pg. 34. Thompson 2-18-44 called stone 3' deep. MCSD 11-12-62 called brass plug. Miller 2-11-76 called same. Gries 11-18-87 called same. Wilcoxen 7-31-92 called same. Excavated by Kiste 7-8-94 brass plug recovered. A wooden hub fd below brass plug. Hole dug 4' dn w/backhoe no stone recovered. Harrison set per 86th St construction project. Retied 9-13-98 by Wilcoxen.

HC731902

REF.	DISTANCE	DESCRIPTION
1.	67.58′	Mag nail w/brass washer W PwP#4-198A 24"up
2.	10.04'	Cut 'x' in median
3.	147.19′	PK w/brass washer N PwP#224-198B 10"up
4.	144.67′	NE corner brick wall
5.	145,36′	Mag nail w/brass washer NW PwP#141-198B 14"up
6.	88.20′	Cut 'x' E sewer manhole rim
7.	50.44	Mag nail w/bw W PwP#15-198 B 12"up
-		